

Applicant(s): LI et al.
Appl. No.: TBD


Remarks

Applicants have made various amendments to the specification. It is respectfully submitted that support for all of these amendments may be found in the specification as originally filed and that none of them constitute the addition of new matter.

Applicants have cancelled Claims 1-7 and have added new Claims 8-29.

Should the Examiner have any questions or believe that a conference would expedite prosecution of this application, he is invited to contact Applicants' undersigned representative.

Respectfully submitted,



Date: February 8, 2005

Jeffrey W. Gluck, Ph.D.
Registration No. 44,457
VENABLE LLP
P.O. Box 34385
Washington, DC 20043-9998
Telephone: (202) 344-4000
Direct Dial: (202) 344-8017
Facsimile: (202) 344-8300

DC2-616326

heading 1;heading 2;heading 3;heading 4;heading 5;heading
6;Default Paragraph Font;?????;header:footer:page number;line
number;Body Text 2;

[0000] This application derives priority from PCT International Application No. PCT/CN2003/000643, filed on August 8, 2003, which designates the United States, and which derives priority from Chinese Application No. 02130031.3, filed on August 10, 2002, both of which are incorporated by reference herein.

Field of the Invention

[0001]The present invention relates to data transmission, particularly to a flow-control method for data traffic transmitted through Synchronous Digital Hierarchy (SDH) network.

Background of the Invention

[0002]As SDH network evolves rapidly, EoS (Ethernet over SDH/SONET) technology is used more and more widely; therefore, how to implement data applications through SDH network efficiently becomes a crucial issue. In Ethernet transmission applications through Metropolitan Area Network (MAN), the distance between two sites can reach 1~2 hundred km, and virtual cascaded mapping pattern for EoS, so the time delay of data transmission between two sites may be as high as several milliseconds or even tens of milliseconds. In addition, Ethernet traffic has outburst feature, i.e.,

- 2 -

instantaneous flow rate maybe very large, therefore the instantaneous flow rate may even exceed the pre-assigned bandwidth.

[0003]Presently, a common flow-control mechanism is CAR (Committed Access Rate), i.e., in case of network congestion, the data beyond the CAR will be discarded by using priority or others like. A disadvantage of the control mechanism is that it often results in severe packet loss, which will severely degrade network performance in common TCP/IP applications; especially for the TCP/IP protocol that is extensively used, packet loss will result in severely degraded application performance. For example, suppose 10M/b Ethernet devices are used in a TCP application and the AckTime is set as 5s, Frame Loss Ratio (FLR) 1% will result in serviceability degraded by 98% for 1,500-Byte Ethernet frames.

[0004]In some ~~network transmission cases~~EoS~~EoS~~ devices, the PAUSE frames generated at a user data device ~~are~~may be transferred to the opposite user data device; however, such data transmission devices directly transfer PAUSE frames generated by user data devices, and said method is only suitable for short distance instead of long distance because ~~the transmission device only transfers~~said PAUSE frames and ~~doesn't generate flow-control information~~will be delayed during transmission; in addition, if the user device at either end doesn't support PAUSE frames, said method can't be used.

[0005]As shown in Fig.1, the EoS device comprises 3 parts: Ethernet access parts, which comprise Physical Layer (PHY) and Media Access Control (MAC); encapsulating and decapsulating parts, the encapsulation may be LAPS (Link Access Protocol-SDH), HDLC (High Level Data Link Control), or GFP (General Framing Procedure), and mapping and demapping parts, the mapping method may be virtual cascading or

cascading.

[0006] Suppose the bandwidth of SDH network is 1 VC3 (i.e., 45M at maximum), if the data transmitting rate of user data device A exceeds 1 VC3, the residue Ethernet frames are stacked at the encapsulating part A because the flow at Mapping part A is constant (1 VC3) according to the prior art; when the cache of encapsulating part A is used up, the data in MAC A can't be sent to encapsulating part A any more; therefore, if Ethernet flow control is enabled, PHY+MAC A will send PAUSE frames (full duplex) or back pressure (half duplex) to user device, shown as the dotted line 1 in Fig.1 (if Ethernet flow control is disabled, MAC A will discard the residue Ethernet frames, referring to IEEE802.3x document for Ethernet flow control), as a result, the transmitting speed of device A will be decreased to below 1 VC3 to prevent packet loss and severely degraded network performance.

[0007] If the transmitting speed of device A is lower than 1 VC3 but the receiving speed of device B is less than the transmitting speed of device A due to certain reasons (for example, device B is attached with a plurality of 10M devices but only one of them is working), the traffic from device A to the transmitting end of EoS device B will not be blocked, instead, device B will be blocked; thus, according to the specification in 802.3x, device B will send 802.3x flow-control information (may be PAUSE frames or back pressure signals) to ports of the EoS device, which is directly connected to it (i.e., the dotted line 2 in Fig.1); according to the specification in 802.3x, the flow-control information will be terminated by MAC B instead of being transferred to device A; at the same time, MAC B will stop sending data to device B ~~and the data will not be transferred to device A,~~ but device A continues sending data at original speed, thus the Ethernet frames from device A stack up at the decapsulating part B or MAC B; when the caches at these

3

- 4 -

positions are used up, packet loss will surely occur at EoS #B; therefore, though both device A and device B are 802.3x Ethernet flow control-supporting devices, packet loss is inevitable after the EoS device. It indicates that traditional 802.3x-based technical solution is unable to ensure Ethernet flow control with EoS devices.

Summary of the Invention

[0008]The object of the present invention is to provide a high-performance flow-control method for data traffic transmitted through SDH network to realize lossless transparent transmission of Ethernet data through SDH network.

[0009]According to the present invention, a flow-control method for data traffic transmitted through SDH network comprises the following steps:

- A. A.—During data transmission through SDH network, the ~~encapsulating part of~~ EoS processing device creating and encapsulating LFP (Line Flow-Control Protocol) frames according to the utilization condition of the frame cache inside;
- B. B.—Said LFP frames being mapped to SDH payload as common data frames and transferred to the opposite device;
- C. C.—Said opposite device demapping the SDH payload, and ~~the decapsulating part of~~ the EoS processing device identifying said LFP frames and phrasing and executing flow control information in the LFP frames.

[00010]Said step of creating and encapsulating LFP frames further comprises the following steps:

[00011]A1. In the uplink direction of said EoS device, the ~~encapsulating part of~~ EoS processing device keeping on

- 5 -

monitoring the data volume in the cache inside and creating LFP frames with corresponding control field; if the data volume exceeds the upper threshold, said encapsulating part periodically sending LFP frames, the control field of which controls to stop sending; if the data volume is lower than the lower threshold, said encapsulating part periodically sending LFP frames, the control field of which controls to start sending; if the data volume is between the lower threshold and the upper threshold, said encapsulating part stops sending LFP frames;

[00012]A2. Said LFP frames are inserted in the head of the data queue to be encapsulated and is given the priority to encapsulate; if no Ethernet frames are being encapsulated, said LFP frames are encapsulated immediately; otherwise they are encapsulated immediately after the current Ethernet frames are encapsulated.

[00013]The carrier of LFP frames can be configured as standard PAUSE frame structure defined by 802.3x.

[00014]The advantage of the present invention is: through LFP frames, flow control information is transferred between EoS devices through the SDH network; the ~~transmission~~EoS devices generate LFP frames and transfer network flow control information between each other so as to achieve lossless transmission of outburst Ethernet data in the SDH network that transmit data periodically, in order to significantly enhance the performance of data applications. The present invention enables transmission of flow control information between EoS devices and also support full duplex or half duplex devices attached to EoS devices, for example, a full duplex device may be attached to one end of the EoS device, and a half duplex device may be attached to the other end of the EoS device, or half duplex devices may be attached to both ends of the EoS device; The EoS processing device keeps on monitoring the data volume in the cache to avoid flow

- 6 -

control failure due to some reasons such as LFP frame transmission failures; therefore, the present invention is a high-performance ~~method for flow control~~ method for data traffic transmitted through SDH network and has high applicability and reliability.

Brief Description of the Drawings

[00015] Fig.1 is a schematic diagram of flow control implemented according to the prior art.

[00016] Fig.2 is a schematic diagram of LFP process according to the present invention.

Detailed Description of the Embodiments

[00017] The present invention will be described in further detail with reference to the following embodiments and the drawings. The present invention will be described with the example of A-B data transmission; the processing method for B-A data transmission is similar.

[00018] In the present invention, during the data transmission through SDH network, the EoS devices transfer flow-control information through LFP frames between them; the carrier of LFP frames can be configured as standard PAUSE frame structure defined by 802.3x.

[00019] During SDH mapping, the mapping part of EoS device processes both Ethernet frames and LFP frames as common data frames; the control field of said LFP frames is 0x0FFFFH or 0x0H and is controlled in a Xon/Xoff control way.

[00020] In addition, because time delay will be generated during LFP frame transmission, appropriate caches are required to compensate the time delay; the LFP frames are implemented on the basis of in-band management, i.e., LFP frames and common Ethernet data frames are transferred through the same transmission paths.

[00021] As shown in Fig.2, in the uplink direction, i.e., the system direction, e.g., the direction of EoS#A - SDH network

- 7 -

in Fig.2, take an example for EoS#A, the ~~encapsulating part of the~~ EoS processing device, according to the lower/upper threshold of frame cache (reflecting utilization of cache), will generate LFP frames, the control field of which is 0x0FFFFH or 0x0H; said LFP frames are processed as common Ethernet data frames in the mapping part of the EoS processing device; however, to enhance the performance of LFP, the priority is given to the LFP frames to send to the mapping part of the EoS processing device; in the downlink direction i.e., the direction to user device, e.g., the direction of SDH - EoS#B in Fig.2, the ~~decapsulating part of the~~ EoS processing device identifies the LFP frames; if the LFP frames are detected, it explains and executes ~~LFP to achieve LFP~~ the flow-control information carried in said LFP frames.

[00022] If the receiving end (i.e., "AR" shown in Fig.2) of user device attached to EoS#A is blocked, the data volume in cache A will increase because the demapping part A continues working normally; when the data volume reaches to the preset upper threshold, the ~~decapsulating part~~ EoS device A will generate LFP frames, the control field of which is 0x0FFFFH, and said LFP frames are inserted in the head of data queue at the encapsulating part A and is given the priority to encapsulate. The process is: if there is no Ethernet frames being encapsulated at the encapsulating part A, said LFP frames will be encapsulated immediately; otherwise said LFP frames will be encapsulated immediately after the current Ethernet frame is encapsulated; then the encapsulated LFP frames will be mapped, transferred from the SDH network and the demapping part B to the decapsulating part B, which identifies the LFP frames and processes it in either of the following ways:

1. 1.—LFP transparent: This way is suitable for the case in which the network delay

- 8 -

is small and the distance between two sites is short. In this way, the ~~decapsulating part~~EoS device B will phrase and execute the LFP frames according to the characteristic of the data device (full duplex or half duplex) attached to it.

[00023] If the user device B attached to the EoS device B works in full duplex mode, the LFP frames will not be phrased, instead, the LFP frames will be directly transferred to the user data device B; the detailed process is: if the decapsulating part B isn't sending data to the Ethernet access part BR, it will send the LFP frames immediately to the Ethernet access part BR; otherwise it will send the LFP frames immediately after the current Ethernet data is sent, in this case, the LFP frames will not pass through cache B in order to enhance its performance.

[00024] If the user data device B attached to the EoS device B works in half duplex mode, the control field of the LFP frames should be phrased, i.e., if it is 0x0H, the back pressure control signal will be canceled; otherwise the back pressure control signal will be sent to make the user device B attached to EoS#B detect a conflict and thus stop transmitting Ethernet data to the ~~encapsulating part~~EoS device B.

[00025] 2. LFP Regeneration: The ~~decapsulating part~~EoS device B phrases and executes the LFP frames; if the control field of the LFP frames is not 0x0H, i.e., ~~LFP~~ the EoS device is disabled from sending data, the encapsulating part will stop working, i.e., it stops receiving data from Ethernet access part BT; ~~if the LFP frames are generated by the decapsulating part B itself, the LFP frames will be sent to the demapping part B~~ hower, if the EoS B device itself generates LFP frames at this time, the encapsulating part B still forwards the LFP

- 9 -

frames to the mapping part B, i.e., in any cases, the LFP frames shall be forward to the mapping part via the encapsulating part-B. Thus the data from Ethernet access part BT will stack up at the encapsulating part B and will finally cause the user device B stopping sending Ethernet frames according to 802.3x Ethernet flow control protocol, i.e., no data will be transmitted to BT; if the control field of the LFP frames is 0x0H, i.e., LFPthe EoS device is enabled to send data, the encapsulating part B will work normally, and encapsulate and send Ethernet frames from the Ethernet access part BT to the mapping part B.

[00026] In this mode, the devices attached to EoS devices at both ends of the SDH network are not required to work in full duplex; instead, they are only required to support standard 802.3x flow control operation. That is to say, the user device at one end may work in full duplex mode while the device at the other end may work in half duplex mode; or the devices at both ends may work in half duplex mode.

[00027] After the user device B attached to EoS#B stops sending data to EoS#B, i.e., there is no Ethernet frame input at BT, the data volume in cache A of EoS#A will be reduced gradually; when the data volume reaches to the lower threshold, the decapsulating part A will generate LFP frames, the control field of which is 0x0H; said LFP frames are given the priority to send to the decapsulating part B in EoS#B and is phrased and executed; as a result, the user device B attached to EoS#B will send data again.

[00028] In order to avoid LFP control failure due to accidents such as LFP frame transmission failures, the EoS processing device keeps on monitoring the data volume in the cache; when the data volume exceeds the upper threshold or is lower than the lower threshold, the EoS processing device will periodically send LFP frames with corresponding control field; if the data volume is between the upper threshold and

9

- 10 -

the lower threshold, the EoS processing device will stop sending LFP frames; if the data volume exceeds the upper threshold, it will periodically send LFP frames, the control field of which is 0x0FFFFH; if the data volume is lower than the lower threshold, it will periodically send LFP frames, the control field of which is 0x0H.

[00029]The lower, upper thresholds and time intervals are configurable, and the time intervals may be different to each other. It is recommended that the time interval for resending LFP frames with the control field 0x0FFFFH should not be too long and the time interval for resending LFP frames with the control field 0x0H should not be too short, so as to avoid excessive occupation of available bandwidth.

[00030]Presently, the format of LFP frames is identical to that of standard 802.3x PAUSE frame in order to simplify LFP frame transparent scheme; however, other formats may also be acceptable if corresponding format conversion at the receiving end in LFP transparent mode is performed; as for LFP frame regeneration scheme, format conversion is unnecessary because the LFP frames are only transferred between EoS devices.

[00031]The present invention is also applicable to SONET network, and the principle and control process are similar. So the case in which the present invention is applied to SONET network will not be described here.

- 14 -

Abstract

A flow-control method for data traffic transmitted through SDH network, wherein: during data transmission through the SDH network, the EoS device generates and encapsulates LFP frames, maps the LFP frames into SDH payload, and transmits the SDH payload to the opposite device, which demaps the LFP frames from the SDH payload and executes the flow control information carried in the LFP frames; the carrier of the LFP frames may be standard PAUSE frame structure defined by 802.3x; LFP frame transparent or LFP frame regeneration may be used when the ~~decapsulating part~~EoS device identifies LFP frames; the present invention is a high-performance method for flow control of data transmission, with high applicability and reliability.

Legend:	
<u>Insertion</u>	
<u>Deletion</u>	
<u>Moved from</u>	
<u>Moved to</u>	
Style change	
Format change	
Moved deletion	
Inserted cell	
Deleted cell	
Moved cell	
Split/Merged cell	
Padding cell	

Statistics:	
	Count
Insertions	48
Deletions	40
Moved from	0
Moved to	0
Style change	0
Format changed	0
Total changes	88